

Excelon®
**Excelprene
 Industrial
 Grade Tubing**



- APPLICATIONS:**
- PERISTALTIC PUMPS
 - WINDOW WASHING SYSTEMS
 - WASTEWATER SAMPLING
 - DISINFECTANT DISPENSING
 - GLASS WASHING SYSTEMS
 - COMMERCIAL DISHWASHING UNITS
 - ABRASION RESISTANT SLEEVES
 - CABLE INSULATION
 - CLEANING CHEMICAL TRANSFER
 - PLATING AND ETCHING CHEMICALS

High-Performance Alternative to General Purpose Rubber

- Equivalent to Tygon® A-60-G
- Long service life with peristaltic pumps
- Excellent flexural fatigue resistance
- Resists cracking when used in vacuum systems
- Abrasion resistant
- Resistant to light and ozone
- Batch consistency

Excelprene TPE Industrial Grade Tubing is high-performance tubing manufactured from a thermoplastic elastomeric compound that consistently outperforms neoprene, EPDM, and other general purpose rubber tubing products. It provides extended service in a wide variety of applications, without weakening or cracking, and can withstand extreme temperatures from -75°F to 275°F.

Typical applications for Excelprene TPE Industrial Grade Tubing include caustic dispensing, wastewater sampling, soap and disinfectant dispensing, transferring printing ink, glass and window washing systems, and more.

PHYSICAL PROPERTIES

PROPERTIES	
Hardness, Shore A, 15 sec, 73 degree F	69
Specific Gravity	.970
Tensile Strength	1000 psi
Elongation at Break	450%
Max. Operating Temp.	275°F
Brittle Temperature	-75°F

Values listed are typical and are meant only as a guide to aid in design. Field testing should be performed to find the actual values for your application.

Samples available upon request.

Custom sizes and lengths available upon request.

REGULATORY COMPLIANCE: REACH, RoHS, and Prop 65 compliant

Excelon®

Excelprene Industrial Grade Tubing



APPLICATIONS:

PERISTALTIC PUMPS

WINDOW WASHING SYSTEMS

WASTEWATER SAMPLING

DISINFECTANT DISPENSING

GLASS WASHING SYSTEMS

COMMERCIAL DISHWASHING UNITS

ABRASION RESISTANT SLEEVES

CABLE INSULATION

CLEANING CHEMICAL TRANSFER

PLATING AND ETCHING CHEMICALS

EXCELPRENE INDUSTRIAL GRADE TUBING SIZING CHART

ITEM NO.	ID	OD	WALL	LENGTH	MINIMUM BEND RADIUS	MAX. WKG PRESSURE PSI @ 73°F
900105BK	.062	.187	.062	50'	.250	34
900205BK	.125	.250	.062	50'	.500	19
900305BK	.187	.312	.062	50'	.750	13
900605BK	.250	.375	.062	50'	1.250	10
900805BK	.250	.500	.125	50'	.750	19
900905BK	.312	.437	.062	50'	1.500	8
901205BK	.375	.500	.062	50'	2.250	7
901405BK	.375	.625	.125	50'	1.250	13
902005BK	.500	.750	.125	50'	2	10
902605BK	.625	.875	.125	50'	3.250	8
903105BK	.750	1	.125	50'	4	7

Values listed are typical and are meant only as a guide to aid in design. Field testing should be performed to find the actual values for your application.

Samples available upon request.

Custom sizes and lengths available upon request.

REGULATORY COMPLIANCE: REACH, RoHS, and Prop 65 compliant



21649 Cedar Creek Ave

Georgetown, DE 19947

P: 302-855-0139

E: tpisales@excelon.com

www.thermoplasticprocesses.com

All contents © 2025 Thermoplastic Processes

LIABILITY CLAUSE

TPI PARTNERS, INC., hereinafter called the "Manufacturer," warrants that its products shall be free from defects in workmanship and materials.

THIS WARRANTY IS IN LIEU OF ALL OTHER WARRANTIES EITHER EXPRESSED OR IMPLIED, INCLUDING WARRANTIES FOR FITNESS FOR PURPOSE INTENDED. The Manufacturer's liability is limited to the replacement of any materials which, after an examination by the Manufacturer and its sole option, are found to be defective. The Manufacturer will honor only those claims which are presented within ninety (90) days of the delivery of the materials to the purchaser. THE MANUFACTURER SPECIFICALLY DISCLAIMS ANY AND ALL LIABILITY FOR CONSEQUENTIAL DAMAGES. This literature supersedes all previous literature and the responsibilities made thereon. CAB-1/02